

## § 58.129

type shall comply with the 3-A Sanitary Standards for Homogenizers and Pumps of the Plunger Type and shall be disassembled and thoroughly cleaned after use.

(o) *New replacement or modified equipment, processing system, or utensils.* All new, replacement, or modified equipment and all processing systems, cleaning systems, utensils, or replacement parts shall comply with the most current, appropriate 3-A Sanitary Standards or 3-A Accepted Practices. If 3-A Sanitary Standards or 3-A Accepted Practices are not available, such equipment and replacements shall meet the general criteria of this section and the USDA Guidelines for the Sanitary Design and Fabrication of Dairy Processing Equipment available from USDA, Agricultural Marketing Service, Dairy Programs, Dairy Grading Branch, or by accessing the Internet at [www.ams.gov/dairy/grade.htm](http://www.ams.gov/dairy/grade.htm).

(p) *Vacuumizing equipment.* The vacuum chamber, as used for flavor control, shall be made of stainless steel or other equally corrosion resistant metal. The unit shall be constructed to facilitate cleaning and all product contact surfaces shall be accessible for inspection. Vacuum chambers located on the pasteurized side of the unit shall be isolated by means of a vacuum breaker and a positive activated check valve on the product inlet side and a vacuum breaker and a positive activated check valve on the discharge side. If direct steam is used, it should also be equipped with a ratio controller to regulate the composition when applicable to the finished product. Only steam which meets the requirements for culinary steam shall be used. The incoming steam supply shall be regulated by an automatic solenoid valve which will cut off the steam supply in the event the flow diversion valve of the pasteurizer is not in the forward flow position. Condensers when used shall be equipped with a water level control and an automatic safety shutoff valve.

[40 FR 47911, Oct. 10, 1975. Redesignated at 42 FR 32514, June 27, 1977, and further redesignated at 46 FR 63203, Dec. 31, 1981, as amended at 67 FR 48974, July 29, 2002]

## 7 CFR Ch. I (1–14 Edition)

### PERSONNEL, CLEANLINESS AND HEALTH

#### § 58.129 Cleanliness.

All employees shall wash their hands before beginning work and upon returning to work after using toilet facilities, eating, smoking or otherwise soiling their hands. They shall keep their hands clean and follow good hygienic practices while on duty. Expectoration or use of tobacco in any form shall be prohibited in each room and compartment where any milk, dairy products, or supplies are prepared, stored or otherwise handled. Clean white or light-colored washable or disposable outer garments and caps (paper caps, hard hats, or hair nets acceptable) shall be worn to adequately protect the hair and beards when grown by all persons engaged in receiving, testing, processing milk, manufacturing, packaging or handling dairy products.

#### § 58.130 Health.

No person afflicted with a communicable disease shall be permitted in any room or compartment where milk and dairy products are prepared, manufactured or otherwise handled. No person who has a discharging or infected wound, sore or lesion on hands, arms or other exposed portion of the body shall work in any dairy processing rooms or in any capacity resulting in contact with milk, or dairy products. Each employee whose work brings him in contact with the processing or handling of dairy products, containers or equipment should have a medical and physical examination by a registered physician or by the local department of health at the time of employment. An employee returning to work following illness from a communicable disease shall have a certificate from the attending physician to establish proof of complete recovery.

### PROTECTION AND TRANSPORT OF RAW MILK AND CREAM

#### § 58.131 Equipment and facilities.

(a)(1) *Milk cans.* Cans used in transporting milk from dairy farm to plant shall be of such construction (preferably seamless with umbrella lids) as